



# 4-264DST DST Hinge 63x50 Pr01 180°



## Avantages

- Hinge with DIRAK-SNAP-Technology.
- For nested doors.
- Hinge visible.
- RH / LH application.
- 180° Opening angle.
- Combination: the short hinge half with DST, the long hinge half with molded in countersunk screws or with countersunk holes.

## Materials

- **Hinge-parts:** zinc die, black
- **Pin:** stainless steel
- **Snap wedges:** sintered steel, zinc plated

## Notes

Allows for corner applications.



## Hinge

	Part Number	Clamping range (S)	Version	Pin version	Installation type	Delivery Unit
a)	418-9103.00-00015	1.2 - 1.7 mm	with molded in screws M6	pressed in	tool-less / screw-on	10 pcs.
a)	418-9103.00-00020	1.7 - 2.2 mm	with molded in screws M6	pressed in	tool-less / screw-on	10 pcs.
a)	418-9103.00-00025	2.2 - 2.7 mm	with molded in screws M6	pressed in	tool-less / screw-on	10 pcs.
a)	418-9103.00-00030	2.7 - 3.2 mm	with molded in screws M6	pressed in	tool-less / screw-on	10 pcs.
b)	418-9102.00-00015	1.2 - 1.7 mm	with countersunk holes for M6	pressed in	tool-less / screw-on	10 pcs.
b)	418-9102.00-00020	1.7 - 2.2 mm	with countersunk holes for M6	pressed in	tool-less / screw-on	10 pcs.
b)	418-9102.00-00025	2.2 - 2.7 mm	with countersunk holes for M6	pressed in	tool-less / screw-on	10 pcs.
b)	418-9102.00-00030	2.7 - 3.2 mm	with countersunk holes for M6	pressed in	tool-less / screw-on	10 pcs.

292-0306.80-02530 **Tool for uninstallation**

292-0401.00-03010 **Cutout-cover**

292-0702.15-01030 **Reinforcement plate for cutout**

