



4-271DST DST Hinge Pr01 180°



Avantages

- For nested doors.
- Hinge visible.
- RH / LH application.
- 180° Opening angle.
- One hinge half with DIRAK-SNAP-Technology, the second hinge half can be adjusted (horizontal / vertical).
- The teeth on the adjusting bushings and in the oblong holes of the second hinge half prevent slipping of the hinge.
- In contrast with conventional oblong holes, the countersunk heads of the screws have full contact with the adjusting bushings.
- These bushings completely cover the oblong holes, preventing deposits of dust within the adjusting area.

Materials

- **Hinge halves and adjusting bushings:** zinc die, black
- **Pin:** stainless steel
- **Snap wedges:** sintered steel

Notes

1. adjusting bushings
Matching arrow tips mark the 0-position.



Hinge

	Part Number	Clamping range (S)	Adjustment	Pin version	Installation type	Delivery Unit
a)	418-9206.00-00020	1.7 - 2.2 mm	horizontal	pressed in	tool-less / screw-on	10 pcs.
a)	418-9206.00-00025	2.2 - 2.7 mm	horizontal	pressed in	tool-less / screw-on	10 pcs.
a)	418-9206.00-00030	2.7 - 3.2 mm	horizontal	pressed in	tool-less / screw-on	10 pcs.
a)	418-9206.00-00035	3.2 - 3.7 mm	horizontal	pressed in	tool-less / screw-on	10 pcs.
b)	418-9207.00-00020	1.7 - 2.2 mm	vertical	pressed in	tool-less / screw-on	10 pcs.
b)	418-9207.00-00025	2.2 - 2.7 mm	vertical	pressed in	tool-less / screw-on	10 pcs.
b)	418-9207.00-00030	2.7 - 3.2 mm	vertical	pressed in	tool-less / screw-on	10 pcs.

292-0301.15-00000 **Tool for uninstallation**

292-0306.80-02530 **Tool for uninstallation**

292-0701.15-01530 **Reinforcement plate for cutout**

