



4-274DST DST Hinge Pr01 270°



Avantages

- Hinge with DIRAK-SNAP-Technology.
- For nested doors.
- Hinge visible.
- RH / LH application.
- 270° Opening angle.
- The short hinge half length is with DST, the long hinge half is with molded in countersunk screws or countersunk holes for M6.

Materials

- **Hinge-parts:** zinc die, black
- **Pin:** stainless steel
- **Snap wedges:** sintered steel, zinc plated



Hinge

	Part Number	Clamping range (S)	Version	Pin version	Installation type	Delivery Unit
a)	418-9205.00-00015	1.2 - 1.7 mm	Screws M8 molded in	pressed in	tool-less / screw-on	10 pcs.
a)	418-9205.00-00020	1.7 - 2.2 mm	Screws M8 molded in	pressed in	tool-less / screw-on	10 pcs.
a)	418-9205.00-00025	2.2 - 2.7 mm	Screws M8 molded in	pressed in	tool-less / screw-on	10 pcs.
a)	418-9205.00-00030	2.7 - 3.2 mm	Screws M8 molded in	pressed in	tool-less / screw-on	10 pcs.
a)	418-9205.00-00035	3.2 - 3.7 mm	Screws M8 molded in	pressed in	tool-less / screw-on	10 pcs.
b)	418-9204.00-00015	1.2 - 1.7 mm	with countersunk holes for M8	pressed in	tool-less / screw-on	10 pcs.
b)	418-9204.00-00020	1.7 - 2.2 mm	with countersunk holes for M8	pressed in	tool-less / screw-on	10 pcs.
b)	418-9204.00-00025	2.2 - 2.7 mm	with countersunk holes for M8	pressed in	tool-less / screw-on	10 pcs.
b)	418-9204.00-00030	2.7 - 3.2 mm	with countersunk holes for M8	pressed in	tool-less / screw-on	10 pcs.
b)	418-9204.00-00035	3.2 - 3.7 mm	with countersunk holes for M8	pressed in	tool-less / screw-on	10 pcs.

292-0301.15-00000 **Tool for uninstallation**

292-0306.80-02530 **Tool for uninstallation**

292-0701.15-01530 **Reinforcement plate for cutout**

