



7-050 Quarter-Turn Pr14.1 L13.5 Stainless Steel



Advantages

- IP65 DIN EN 60529 by sealing kit (optional).
- RH / LH application.
- On request parts can be assembled by DIRAK.
- A pre-assembled quarter-turn can be installed in the cutout and combined with finger pull of product system 1-060.

Materials

- **Housing and insert** : AISI 316
- **Screw, serrated washer**: AISI 304
- **Wave washer and cam**: AISI 301

Remarks

With assembled cam - door thickness (S) max. 2mm
With unasssembled cam - door thickness (S) max. 5mm
When using finger pull (f) the H-dimension decreases by 0.8mm!
Please configure the quarter-turn with insert and cam.



Quarter-Turn housing + nut

	Part Number	Housing length	Installation type	Delivery Unit
a)	220-9018.00-00000	13.5 mm	screw-on	1 pc.


Insert with screw, spring- and serrated washer

	Part Number	Insert	Delivery Unit
c)	220-9120.00-00000	Square 6mm	1 pc.
d)	220-9121.00-00000	Triangular 6.5mm	1 pc.
e)	220-9122.00-00000	Slotted 1,5x3mm	1 pc.

Cams L24, with stop

	Part Number	H-dimension	Delivery Unit
b)	220-0503.04-00000	7.5 mm	1 pc.
b)	220-0501.04-00000	13.5 mm	1 pc.
b)	220-0502.04-00000	19.5 mm	1 pc.

Function

 extension

f) 209-9003.00-00000 **Sealing kit IP65 for Quarter-Turns Pr14.1**

Assembly options

220-0001.00-00000 **Assembling cam without o-ring**

220-0002.00-00000 **Assembling cam with o-ring**

Accessories

g) 220-1301.00-00000 **Finger pull**

6-100 **Wrenches and Keys**

